



The Effects of Aerodynamic Jump Caused by a Uniform Sequence of Lateral Impulses

by Gene R. Cooper

ARL-TR-3206

July 2004

NOTICES

Disclaimers

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

Citation of manufacturer's or trade names does not constitute an official endorsement or approval of the use thereof.

DESTRUCTION NOTICE—Destroy this report when it is no longer needed. Do not return it to the originator.

Army Research Laboratory

Aberdeen Proving Ground, MD 21005-5066

ARL-TR-3206**July 2004**

The Effects of Aerodynamic Jump Caused by a Uniform Sequence of Lateral Impulses

Gene R. Cooper

Weapons and Materials Research Directorate, ARL

REPORT DOCUMENTATION PAGE				Form Approved OMB No. 0704-0188	
<p>Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.</p> <p>PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.</p>					
1. REPORT DATE (DD-MM-YYYY) July 2004		2. REPORT TYPE Final		3. DATES COVERED (From - To)	
4. TITLE AND SUBTITLE The Effects of Aerodynamic Jump Caused by a Uniform Sequence of Lateral Impulses				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S) Gene R. Cooper (ARL)				5d. PROJECT NUMBER 622618.H8000	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory Weapons and Materials Research Directorate Aberdeen Proving Ground, MD 21005-5066				8. PERFORMING ORGANIZATION REPORT NUMBER ARL-TR-3206	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT The linear theory for spinning projectiles is extended to account for the application of a uniform sequence of lateral square impulses activated during free flight. Analytical results are shown to produce simple contributions to the familiar aerodynamic jump formulation for a single impulse. Inquiries regarding modifications of jump smearing are addressed, and comparative calculations are presented. The formulation shows that an additional jump phase angle and the jump magnitude are changed by a multiplying factor describing the impulse sequence.					
15. SUBJECT TERMS impulse; jump; linear theory					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT UL	18. NUMBER OF PAGES 20	19a. NAME OF RESPONSIBLE PERSON Gene R. Cooper
a. REPORT Unclassified	b. ABSTRACT Unclassified	c. THIS PAGE Unclassified			19b. TELEPHONE NUMBER (Include area code) 410-278-3684

Standard Form 298 (Rev. 8/98)

Prescribed by ANSI Std. Z39.18

Contents

List of Figures	iv
1. Introduction	1
2. Projectile Dynamic Model	1
3. Pulse Force and Moment Conditions	2
4. Changes Caused by a Sequence of Lateral Pulses	6
5. Conclusions	9
6. References	10
Appendix A. Flight Coefficients for a 40-mm Projectile	11
Symbols	13
Distribution List	15

List of Figures

Figure 1. Projectile position coordinate definition.	5
Figure 2. Projectile orientation definition.	5
Figure 3. Jump component-J because of lateral impulse versus impulse duration.	7
Figure 4. Jump component-K because of lateral impulse versus impulse duration.	8
Figure 5. Jump magnitude because of lateral impulse versus impulse duration.	9

1. Introduction

This report extends the papers by Cooper (1) and Cooper and Costello (2) which examined the aerodynamic jump characteristics of a spinning projectile subjected to a single lateral impulse. The extension considers a sequence of lateral impulses, each separated by a constant arc length T . Jump effects attributable to gravity have now been included since experience has shown that when one ignores gravity, as is usually done, it may lead to incorrect results (3). The modification parallels the analysis of Cooper (1) and Cooper and Costello (2) where the changes in the analysis stem from the impulse sequence driving terms and a corrected limiting procedure that retains the pertinent gravity terms influencing aerodynamic jump.

2. Projectile Dynamic Model

The analysis here follows the same analysis presented in Cooper and Costello, and the equations of motion continue to have the following form for the linear theory (see figures 1 and 2):

$$\begin{Bmatrix} \tilde{u} \\ \tilde{v} \\ \tilde{w} \end{Bmatrix} = \begin{Bmatrix} 1 & 0 & 0 \\ 0 & \cos \phi & \sin \phi \\ 0 & -\sin \phi & \cos \phi \end{Bmatrix} \begin{Bmatrix} u \\ v \\ w \end{Bmatrix} \quad (1)$$

$$x' = D \quad (2)$$

$$y' = \frac{D}{V} \tilde{v} + D\psi \quad (3)$$

$$z' = \frac{D}{V} \tilde{w} - D\theta \quad (4)$$

$$\phi' = \frac{D}{V} p \quad (5)$$

$$\theta' = \frac{D}{V} \tilde{q} \quad (6)$$

$$\psi' = \frac{D}{V} \tilde{r} \quad (7)$$

$$V' = \frac{\rho S D C_{x0}}{2m} V - G\theta \quad (8)$$

$$p' = \frac{\rho S D^2 C_{LDD}}{2I_x} V + \frac{\rho S D^3 C_{LP}}{4I_x} p \quad (9)$$

$$\begin{Bmatrix} \tilde{v}' \\ \tilde{w}' \\ \tilde{q}' \\ \tilde{r}' \end{Bmatrix} = \begin{bmatrix} -A & 0 & 0 & -D \\ 0 & -A & D & 0 \\ B/D & C/D & E & -F \\ -C/D & B/D & F & E \end{bmatrix} \begin{Bmatrix} \tilde{v} \\ \tilde{w} \\ \tilde{q} \\ \tilde{r} \end{Bmatrix} + \begin{Bmatrix} Y_I \\ Z_I + G \\ M_I \\ N_I \end{Bmatrix} \quad (10)$$

$$\begin{Bmatrix} A \\ B \\ C \\ E \\ F \end{Bmatrix} = \begin{Bmatrix} \frac{\pi \rho D^3 C_{NA}}{8m} \\ \frac{\pi \rho p D^5 C_{YPA} SLCOM}{16 I_y V_0} \\ \frac{\pi \rho D^4 C_{NA}}{8 I_y} \\ \frac{\pi \rho D^5 C_{MQ}}{16 I_y} \\ \frac{p D I_x}{I_y V_0^2} \end{Bmatrix} \quad (11)$$

Following the usual linear assumptions, the forward velocity and projectile roll rate are taken to be constant (4), i.e., $V \approx V_0$, $p \approx p_0$.

3. Pulse Force and Moment Conditions

The pulse forces applied to the projectile are taken to be lateral impulsive forces and each force is attributable to an actuator attached to the projectile body (see the source terms of equation 10). For this investigation, the force actuators are modeled as a sequence of scaled square wave pulses of length L_n and actuated at $s_n + jT$, making the resulting force and moment components in the non-rolling frame

$$Y_I = \frac{F^* V_0 \sum_{j=0}^{K_m} [\text{sgn}(s - s_n - jT) - \text{sgn}(s - s_n - L_n - jT)] \cos\left(\frac{Dp}{V_0} s + \phi_B\right)}{2L_n} \quad (12)$$

$$Z_I = \frac{F^* V_0 \sum_{j=0}^{K_m} [\text{sgn}(s - s_n - jT) - \text{sgn}(s - s_n - L_n - jT)] \sin\left(\frac{Dp}{V_0} s + \phi_B\right)}{2L_n} \quad (13)$$

$$M_I = - \frac{M^* V_0 \sum_{j=0}^{K_m} [\text{sgn}(s-s_n-jT) - \text{sgn}(s-s_n-L_n-jT)] \sin\left(\frac{Dp}{V_0}s + \phi_B\right)}{2DL_n} \quad (14)$$

$$N_I = \frac{M^* V_0 \sum_{j=0}^{K_m} [\text{sgn}(s-s_n-jT) - \text{sgn}(s-s_n-L_n-jT)] \cos\left(\frac{Dp}{V_0}s + \phi_B\right)}{2DL_n} \quad (15)$$

$$F^* = \frac{DF_d}{mV_0^2} \quad (16)$$

$$M^* = \frac{D^2 F_d X_r}{I_y V_0^2} \quad (17)$$

Note that the last expressions are equivalent to delta function impulses in the limit of $L_n \rightarrow 0$.

Swerving motion is measured along the earth-fixed \mathbf{J}_I and \mathbf{K}_I axes. To an observer standing behind the gun tube, these axes are oriented so that positive \mathbf{J}_I is to the right and positive \mathbf{K}_I is pointed downward. The swerving motion results from a combination of the normal aerodynamic forces, as the projectile pitches and yaws, plus the forces and moments attributable to the applied impulses. Swerving motion is thus described by the following equations (1,2,4):

$$\frac{y''}{D} = \frac{F_I \cos(\phi_B) \sum_{j=0}^{K_m} [\text{sgn}(s-s_n-jT) - \text{sgn}(s-s_n-L_n-jT)]}{2L_n} - \frac{A\tilde{v}}{V_0} \quad (18)$$

$$\frac{z''}{D} = \frac{F_I \sin(\phi_B) \sum_{j=0}^{K_m} [\text{sgn}(s-s_n-jT) - \text{sgn}(s-s_n-L_n-jT)]}{2L_n} + \frac{G - A\tilde{w}}{V_0} \quad (19)$$

For a stable projectile, the swerve caused by epicyclical vibration decays as the projectile progresses down range and does not affect the long-term lateral motion of the projectile. Long-term center of mass solution, or swerve, contains terms that remain bound with arc length s plus terms that are linear with s , and if the total gravity contribution is included, the solution will have higher order diverging terms. These higher order terms are typically denoted as gravity drop and are generally ignored since they are well understood. The linear terms are called aerodynamic jump, caused by initial conditions at the gun muzzle, lateral pulse forces, and aerodynamic characteristics. Setting the diverging gravity terms to zero and subsequently evaluating the following limits formally define aerodynamic jump

$$\lim_{s \rightarrow \infty} \frac{y(s)}{Ds} = \Gamma_J \quad \lim_{s \rightarrow \infty} \frac{z(s)}{Ds} = \Gamma_K \quad (20)$$

When a lateral pulse is applied to the projectile at arc length s_n , its effect on the target impact point is predominantly attributable to aerodynamic jump because damping rates and target distance are sufficient to allow the epicyclical transients to decay. As shown in equation 21, each of the two components of aerodynamic jump is expressed with terms attributable to muzzle conditions and linear gravity effects, plus a term attributable to the uniform sequence of lateral pulse forces and moments:

$$\begin{aligned} \begin{Bmatrix} \Gamma_J \\ \Gamma_K \end{Bmatrix} = & -\frac{A}{[(AF+B)^2 + (AE+C)^2] V_0} \begin{Bmatrix} AF+B & -AE-C \\ AE+C & AF+B \end{Bmatrix} \begin{Bmatrix} v_0 F + w_0 E - q_0 D \\ w_0 F - v_0 E - r_0 D \end{Bmatrix} - \\ & \frac{AG}{[(AF+B)^2 + (AE+C)^2] V_0} \begin{Bmatrix} (AF+B)^2 - (AE+C)^2 & -2(AE+C)(AF+B) \\ 2(AE+C)(AF+B) & (AF+B)^2 - (AE+C)^2 \end{Bmatrix} \begin{Bmatrix} 2EF+B \\ F^2 - E^2 - C \end{Bmatrix} + \\ & \Lambda \begin{Bmatrix} \cos \Pi \\ -\sin \Pi \end{Bmatrix} \end{aligned} \quad (21)$$

in which

$$\begin{aligned} Y &= \frac{(AF+B)(A(X_I - 3C) - 4C) + (AE+C)(3AF + 4B)}{(AF+B)^2 + (AE+C)^2} \\ Z &= \frac{(AF+C)(A(X_I - 3C) - 4C) - (AE+B)(3AF + 4B)}{(AF+B)^2 + (AE+C)^2} \\ \Pi &= \frac{P(L_n + KmT)}{2} + Ps_n + \phi_B - \tan^{-1}(\Sigma_K / \Sigma_J) \\ \Lambda &= \sqrt{Y^2 + Z^2} \frac{FF \sin\left(\frac{PL_n}{2}\right) \sin\left(\frac{P(Km+1)T}{2}\right)}{(PL_n/2) \sin\left(\frac{PT}{2}\right)} \end{aligned} \quad (22)$$

The magnitude, Λ , and phase angle, $\tan^{-1}(\Gamma_K / \Gamma_J)$, of the jump component are calculated from equation 22.




Figure 1. Projectile position coordinate definition.




Figure 2. Projectile orientation definition.

4. Changes Caused by a Sequence of Lateral Pulses

To examine the swerve response resulting from a sequence of lateral pulses, it is helpful to write the last term in equation 21 in complex form

$$\Delta (\cos \Pi - i \sin \Pi) = \frac{i e^{i\Delta} \sin\left(\frac{P L_n}{2}\right) (A M M - (C + i B) F F) \sin\left(\frac{P T (K_m + 1)}{2}\right)}{(P L_n / 2) (A F - i C + B) \sin\left(\frac{P T}{2}\right)} \quad (23)$$

$$\Delta = \frac{P(L_n + K_m T)}{2} + P s_n + \phi_B$$

The last expression shows that the jump attributable to $K_m + 1$ impulses is simply the result of a single impulse multiplied by

$$\Re = \frac{e^{\frac{i P K_m T}{2}} \sin\left(\frac{P T (K_m + 1)}{2}\right)}{\sin\left(\frac{P T}{2}\right)} \quad (24)$$

The most important features of equally spaced multiple impulses are found by examination of the last equation for various values of T and K_m . To emphasize the smearing effects, the roll position, ϕ_N , of the lateral impulse force is assumed to act primarily along the non-rolling Y -axis. This means the arc length, s_N , corresponding to the center of the pulse satisfies the expression $\phi_N = \phi' s_N + \phi_B = 2\pi N$, $N = 0, 1, 2, \dots$. To assure that this force is acting nominally along the non-rolling Y -axis, the activation point begins at $s_n = s_N - L_n/2$ so that the duration of the impulse brackets $\phi_N = 2\pi N$.

Assuming that all multiple impulses bracket $\phi_N = 2\pi N$ means that the separation arc length must be $T = 2\pi N/P$, and an inspection of equation 24 shows $\Re = K_m + 1$. This makes physical sense because repeated impulses in the same direction should result in a jump that is $K_m + 1$ times the jump for a single impulse. Considering cases when successive impulses are activated at $\phi_N = 2\pi N + \text{integer } \pi$ implies that one way to do this is to let $T = \pi(2N + 1)/P$. Equation 24 leads directly to

$$\Re = e^{\frac{i \pi K_m}{2}} \cos\left(\frac{\pi K_m}{2}\right) \text{ or } \Re = \begin{cases} 1 \rightarrow K_m \text{ even} \\ 0 \rightarrow K_m \text{ odd} \end{cases},$$

which also confirms physical reasoning.

Plots comparing the effect of smearing between a one- and a two-impulse sequence, $K_m = 0, 1$ are given in figures 3 and 4 for the applied force $F^* = 3.836 \times 10^{-5}$ and moment arm

$X_r/D = -0.635$ (see appendix A). These parameters correspond to the case in Cooper's (1,2) report for which the jump resulting from a single impulse was greatest. Negative values of X_r indicate that the application point of the pulse force is aft of the mass center. The chosen value

$$T = \frac{3\pi}{2P}$$

shows that a sequence of impulses can cause considerable changes in both Γ_j and Γ_k and these in turn impact the phase angle $\tan^{-1}(\Gamma_k/\Gamma_j)$ because of the pre-multiplier $e^{\frac{iPK_mT}{2}}$ in equation 24. Changes in the phase angle response are readily seen so that the phase angle from a single impulse is shifted by $\frac{PK_mT}{2}$ for K_m additional impulses. In this example, i.e.,

$T = \frac{3\pi}{2P}$, $K_m = 2$, the phase is shifted by $\frac{3\pi}{2}$ or increased by 270 degrees.




Figure 3. Jump component-J because of lateral impulse versus impulse duration.




Figure 4. Jump component-K because of lateral impulse versus impulse duration.

Figure 5 gives a chart showing the respective magnitudes, $|\Lambda|$, of the two sample cases given here. These clearly show that repeated impulses that do not bracket $\phi_N = 2\pi N$ can greatly impact the direction of jump induced by lateral impulses. In any case, the magnitude has changed by the factor

$$\frac{\sin\left(\frac{PT(K_m+1)}{2}\right)}{\sin\left(\frac{PT}{2}\right)}.$$

Increasing pulse length, L_n , causes the jump components to cyclically decay while the value of L_n at $L_n = 0$ corresponds to a lateral impulse that is proportional to the delta function $\delta(s - s_n)$. Values of L_n where the jump is zero represent situations when the duration of the lateral pulse coincides with a roll cycle. Notice for the case presented that the response attributable to a two-sequence pulse has a predominant direction that depends on the particular choices of T and sequence length K_m .




Figure 5. Jump magnitude because of lateral impulse versus impulse duration.

5. Conclusions

The analytical approach for quantifying the effect of a uniform sequence of lateral square impulses disturbing a projectile during free flight is presented. All the analysis was based on projectile linear theory, which produces simple closed form solutions for the assumed square pulse disturbances. The swerving motion caused by a single impulse (I) is modified by a multiplying factor, equation 24, which accounts for a uniform sequence, length $K_m + 1$, of impulses. Changes in aerodynamic jump caused by a sequence of lateral impulse forces are shown to produce easy-to-understand additive contributions to the usual aerodynamic jump. Magnitude and phase angle changes that depend on the sequence length and spacing are readily obtained, which may prove useful guidance, navigation, and control.

6. References

1. Cooper, G. R. *Projectile Aerodynamic Jump Due to Lateral Impulsives*; ARL-TR-3087; U.S. Army Research Laboratory: Aberdeen Proving Ground, MD, 2003.
2. Cooper, G. R.; Costello, M. Flight Dynamic Response of Spinning Projectiles to Lateral Impulsive Loads; to be published, Sept. 2004 DS-03-1056, *Journal of Dynamic Systems, Measurement and Control*, American Society of Mechanical Engineers.
3. Plostins, P. U.S. Army Research Laboratory: Aberdeen Proving Ground, MD, private communication.
4. Murphy, C. H. *Free Flight Motion of Symmetric Missiles*; BRL Report No. 1216; U.S. Army Ballistic Research Laboratory: Aberdeen Proving Ground, MD, 1963.

Appendix A. Flight Coefficients for a 40-mm Projectile

The numerical values used for the graphical presentations given in this report are shown in the following matrices:

Aerodynamic coefficients:

$$\mapsto \begin{Bmatrix} C_{X0} \\ C_{X2} \\ C_{NA} \\ C_{YPA} \\ C_{LP} \\ C_{MQ} \end{Bmatrix} = \begin{Bmatrix} 0.279 \\ 2.672 \\ 2.329 \\ -0.295 \\ -0.042 \\ -1.800 \end{Bmatrix}. \quad (\text{A-1})$$

Physical parameters:

$$\mapsto \begin{Bmatrix} m \\ I_X \\ I_Y \\ D \\ SL_{COP} \\ SL_{MAG} \\ SL_{CG} \end{Bmatrix} = \begin{Bmatrix} 0.0116 \text{ Slug} \\ 2.85 \times 10^{-5} \text{ Slug ft.}^2 \\ 2.72 \times 10^{-5} \text{ Slug ft.}^2 \\ 0.137 \text{ ft.} \\ 0.237 \text{ ft.} \\ 0.239 \text{ ft.} \\ 0.0713 \text{ ft.} \end{Bmatrix}. \quad (\text{A-2})$$

Flight characteristics:

$$\mapsto \begin{Bmatrix} \rho \\ V_0 \\ p \end{Bmatrix} = \begin{Bmatrix} 2.38 \times 10^{-3} \text{ Slug ft.}^{-3} \\ 250.0 \text{ ft. sec.}^{-1} \\ 399.7 \text{ sec.}^{-1} \end{Bmatrix}. \quad (\text{A-3})$$

INTENTIONALLY LEFT BLANK.

Symbols

C_i	Projectile aerodynamic coefficients
D	Projectile characteristic length (diameter)
F_d	Dimensional impulse force
F^*	Non-Dimensional impulse force $F^* = DF_d / mV_0^2$
g	Gravitational constant
G	Scaled gravitational constant $G = gD/V_0$
I_x	Mass moments of inertia
I_y	
L	Applied moments about projectile mass center expressed in the no-roll frame
\tilde{M}	
\tilde{N}	
m	Projectile mass
P	Non-dimensional spin rate $P = Dp/V_0$
p	Angular velocity components vector of projectile in the no-roll frame
\tilde{q}	
\tilde{r}	
S	Surface area $S = \pi D^2/4$
u	Mass center velocity components in the body reference frame
v	
w	
V_0	Forward velocity of projectile
u	Mass center velocity components in the no-roll reference frame
\tilde{v}	
\tilde{w}	
X_r	Dimensional moment arm length
Y_1	Applied force components in the no-roll reference frame
Z_1	
$\begin{Bmatrix} x \\ y \\ z \end{Bmatrix}$	Position vector of body center of mass in an inertial reference frame

α	Longitudinal aerodynamic angle of attack
β	Lateral aerodynamic angle of attack
Γ_J	J
Γ_K	K
	Components of aerodynamic jump
Π	Phase angle of the aerodynamic jump caused by a lateral impulse
Σ	Magnitude of jump caused by a lateral impulse
ϕ	
θ	Euler roll, pitch and yaw angles of the projectile
ψ	
ϕ_B	Euler roll angle of the applied impulse

NO. OF
COPIES ORGANIZATION

- * ADMINISTRATOR
DEFENSE TECHNICAL INFO CTR
ATTN DTIC OCA
8725 JOHN J KINGMAN RD STE 0944
FT BELVOIR VA 22060-6218
*pdf file only
- 1 DIRECTOR
US ARMY RSCH LABORATORY
ATTN AMSRD ARL CI IS R REC MGMT
2800 POWDER MILL RD
ADELPHI MD 20783-1197
- 1 DIRECTOR
US ARMY RSCH LABORATORY
ATTN AMSRD ARL CI OK TECH LIB
2800 POWDER MILL RD
ADELPHI MD 20783-1197
- 2 USAF WRIGHT AERONAUTICAL
LABORATORIES
ATTN AFWAL FIMG DR J SHANG
MR N E SCAGGS
WRIGHT PATTERSON AFB OH 45433-6553
- 1 COMMANDER
NAVAL SURFACE WARFARE CNTR
ATTN CODE B40 W YANTA
DAHLGREN VA 22448-5100
- 1 COMMANDER
NAVAL SURFACE WARFARE CNTR
ATTN CODE 420 A WARDLAW
INDIAN HEAD MD 20640-5035
- 4 DIR NASA LANGLEY RSCH CTR
ATTN TECH LIBRARY
D M BUSHNELL
M J HEMSCH J SOUTH
LANGLEY STATION
HAMPTON VA 23665
- 4 DIR NASA AMES RSCH CTR
ATTN T 27B-1 L SCHIFF
T 27B-1 T HOLST
MS 237-2 D CHAUSSEE
MS 258 M. RAI
MOFFETT FIELD CA 94035
- 3 DIR NASA AMES RSCH CTR
ATTN MS 258 1 B MEAKIN
MS T27B-2 M. AFTOSMIS
MS T27B-2 J. MELTON
MOFFETT FIELD CA 94035

NO. OF
COPIES ORGANIZATION

- 3 AIR FORCE ARMAMENT LAB
ATTN AFATL/FXA S C KORN
B SIMPSON D BELK
EGLIN AFB FL 32542-5434
- 4 CDR US ARMY TACOM ARDEC
ATTN AMSTA AR FSF T C NG
J GRAU H HUDGINS
W KOENIG
BLDG 382
PICATINNY ARSENAL NJ 07806-5000
- 2 AFRL/MNAV
ATTN G ABATE
J ANTONEN
101 W EGLIN BLVD STE 219
EGLIN AIR FORCE BASE FL 32542
- 1 CDR US ARMY TACOM
ATTN AMSTA-AR-CCH-B P VALENTI
BLDG 65-S
PICATINNY ARSENAL NJ 07806-5001
- 1 CDR US ARMY ARDEC
ATTN SFAE FAS SD M DEVINE
PICATINNY ARSENAL NJ 07806-5001
- 1 AEROPREDICTION INC
ATTN F MOORE
9449 GROVER DR STE 201
KING GEORGE VA 22485
- 2 UNIV OF CALIFORNIA DAVIS
DEPT OF MECHANICAL ENGG
ATTN PROF H A DWYER
PROF M HAFEZ
DAVIS CA 95616
- 1 AEROJET ELECTRONICS PLANT
ATTN D W PILLASCH
B170 DEPT 5311
PO BOX 296
1100 WEST HOLLYVALE ST
AZUSA CA 91702
- 1 MASS INST OF TECHNOLOGY
ATTN TECH LIBRARY
77 MASSACHUSETTS AVE
CAMBRIDGE MA 02139
- 1 LOS ALAMOS NATL LAB
ATTN WM HOGAN
MS G770
LOS ALAMOS NM 87545

NO. OF COPIES	ORGANIZATION
3	DIR SANDIA NATL LABORATORIES ATTN DIV 1554 DR W OBERKAMPF DIV 1554 DR F BLOTTNER DIV 1636 DR W WOLFE ALBUQUERQUE NM 87185
1	NAVAL AIR WARFARE CENTER ATTN D FINDLAY MS 3 BLDG 2187 PATUXENT RIVER MD 20670
1	METACOMP TECHNOLOGIES INC ATTN S R CHAKRAVARTHY 650 HAMPSHIRE RD SUITE 200 WESTLAKE VILLAGE CA 91361-2510
1	ADVANCED TECHNOLOGY CTR ARVIN/CALSPAN AERODYNAMICS RSCH DEPT ATTN M S HOLDEN PO BOX 400 BUFFALO NY 14225
1	UNIV OF ILLINOIS AT URBANA CHAMPAIGN DEPT OF MECHANICAL AND INDUSTRIAL ENGINEERING ATTN J C DUTTON URBANA IL 61801
1	UNIV OF MARYLAND DEPT OF AEROSPACE ENGG ATTN J D ANDERSON JR COLLEGE PARK MD 20742
1	UNIV OF TEXAS DEPT OF AEROSPACE ENG MECHANICS ATTN D S DOLLING AUSTIN TX 78712-1055
1	CDR US ARMY TACOM-ARDEC ATTN AMCPM DS MO P J BURKE BLDG 162S PICATINNY ARSENAL NJ 07806-5000
1	CDR USAAMCOM ATTN AMSAM RD SS G LANDINGHAM REDSTONE ARSENAL AL 35898-5252
2	ARROW TECH ASSOCIATES ATTN W HATHAWAY R WHYTE 1233 SHELBURNE RD STE D-8 SOUTH BURLINGTON VT 05403

NO. OF COPIES	ORGANIZATION
	<u>ABERDEEN PROVING GROUND</u>
1	DIRECTOR US ARMY RSCH LABORATORY ATTN AMSRD ARL CI OK (TECH LIB) BLDG 4600
2	DIR USARL ATTN AMSRD ARL WM JILL SMITH T ROSENBERGER BLDG 4600
1	DIR USARL ATTN AMSRD ARL WM B A W HORST JR BLDG 4600
1	DIR USARL ATTN AMSRD ARL WM BA D LYON BLDG 4600
2	DIR USARL ATTN AMSRD ARL WM BC P PLOSTINS J SAHU BLDG 390
1	DIR USARL ATTN AMSRD ARL CI H C NIETUBICZ BLDG 328
1	DIR USARL ATTN AMSRD ARL CI HC R NOAK BLDG 394
3	CDR US ARMY ARDEC FIRING TABLES BRANCH ATTN R LIESKE R EITMILLER F MIRABELLE BLDG 120
6	DIR USARL ATTN AMSRD ARL WM B GUIDOS M BUNDY G COOPER P WEINACHT SIDRA SILTON XIAOGAN HUANG BLDG 390